

## Wall Tie Fill and Sealing Compound

ADOPLUG is a polymer modified, fibre reinforced, cementitious powder designed specifically for plugging tie holes.

When mixed with water it forms a cohesive, easy to apply, shrinkage compensated compound and cures to develop a strongly bonded watertight plug to form an effective seal.

## Application

### Preparation of Hole

The concrete surface to which the ADOPLUG will be in contact should be sound, free of dirt and any other contaminants and well dampened down to minimise suction. When filling holes formed by through ties plastic pipe remaining in the wall should either be removed or drilled back to approximately 50mm from the concrete face and then plugged with a tie stopper or similar to form a backing for compacting the ADOPLUG against.

A depth of 50mm is suitable for water heads of up to 3m. For pressures in excess of this the depth should be increased, typically by 50mm for each additional 2m until complete filling is achieved. Particular care should be taken to ensure a well keyed surface within the tie hole.

### Mixing

The ideal mix is of a stiff cohesive consistency and this is achieved at approximately 5 to 1 by weight, mixing the powder gradually into the water. To achieve the desired consistency more water will be required in hard water areas than in soft water areas.

### Application

Using a trowel or similar, place a quantity of ADOPLUG into the dampened hole and compact well by means of a steel rod, repeating the operation until the hole is completely filled with well compacted ADOPLUG, then trowel to the required finish.

ADOPLUG will set in less than 45 minutes (at normal temperatures) so only mix as much as can be placed and finished in 20 minutes.

### Curing

Due to moisture retention of the polymer no special curing procedure is generally necessary excepting in high ambient temperatures or windy conditions when it is advisable to take precaution to prevent rapid drying of the compound.

## Coverage

2kg will fill approximately 1,2 by 1mm deep.

## Storage

Store in dry conditions and keep container sealed when not in use.

## Shelf Life

Shelf life when stored correctly is 12 months for pails and 6 months for sacks.

## Specification

ADOPLUG is manufactured by Adomast Manufacturing Ltd and shall be applied strictly in accordance with the manufacturer's instructions. For specific advice regarding any aspect of this product, please consult our Technical Department

## Health and Safety

Prolonged physical contact should be avoided and personal and environmental hygiene encouraged. Where contact with skin occurs, the material should be removed with soap and water. If powder affects the eyes, they should be bathed immediately with copious quantities of clean water and if discomfort persists, medical attention should be sought without delay.

See Safety Data Sheet for further information.